GOLD BT 5W30



This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices (Compatible with DPF).



APPLICATIONS

This dexos 2TM approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2TM specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2TM lubricants. C2* meets all engine protection requirements of ACEA C2.

PERFORMANCE LEVEL

ACEA: C2/C3

API: SN/CF

BMW: LONGLIFE-04

• VW: 502 00

• VW: 505 00

• VW: 505 01

• Opel: OV0401547

• GM: DEXOS 2

• MB: 229.51

• MB: 229.52

• RENAULT: RN17 Level

CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.851
Viscosity 40°C	mm²/s	72.60
Viscosity 100°C	mm²/s	12.50
Viscosity -30°C	mPas	6136
Viscosity index		172
Flash point COC	°C	230
Pour point	°C	-36
Total base number	mgKOH/g	7.4
Sulphated ash content	%	0.78

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in echnology.	