

GOLD MAX 5W30



This is a full synthetic lubricant based on carefully selected very high quality base oils, providing outstanding wear and sludge protection, even under the most severe driving conditions. Due to its enhanced frictional properties, improved fuel economy is obtained.



APPLICATIONS

This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.

PERFORMANCE LEVEL

- **API: SN/CF**
- **ACEA: A3/B4**
- **VW 502.00 / 505.00**
- **MB 229.3 / 226.5**
- **BMW: Longlife-01**
- **OPEL GM-LL-B-25**
- **RENAULT 0700**

CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.856
Viscosity 40°C	mm ² /s	64.3
Viscosity 100°C	mm ² /s	10.9
Viscosity -30°C	mPas	6300
Viscosity index		162
Flash point COC	°C	228
Pour point	°C	-45
Total base number	mgKOH/g	8.1
Sulphated ash content	%	0.88

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be