

## GREEN G2 5W20



A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming



### APPLICATIONS

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2

### PERFORMANCE LEVEL

- **API: SP Resource Conserving**
- **ILSAC: GF-6A**
- **GM: DEXOS 1 (TM) GEN 2**
- **CHRYSLER: MS6395**
- **FORD: WSS-M2C945A/B1 / WSS-M2C960-A1**
- **FIAT: 9.55535-CR1**

### CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.852
Viscosity 40°C	mm <sup>2</sup> /s	48.00
Viscosity 100°C	mm <sup>2</sup> /s	8.80
Viscosity -30°C	mPas	3940
Viscosity index		158
Flash point COC	°C	226
Pour point	°C	-33
Total base number	mgKOH/g	8.5
Sulphated ash content	%	0.89

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

### PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be