

## SILVER SN 10W40



This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- High and stable viscosity index
- A fast cold start
- A strong oxidation resistance
- Good detergency and dispersion
- A safe lubrication film at high temperatures
- A strong anti-wear, corrosion and foaming



### APPLICATIONS

This lubricant is suitable for petrol, LPG and diesel engines, with or without turbo charging, in passenger cars and vans.

### PERFORMANCE LEVEL

- ACEA A3/B4
- API SN/CF
- MB 229.1
- RN0700
- VW501.01/505.00

### CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.860
Viscosity 40°C	mm <sup>2</sup> /s	90.40
Viscosity 100°C	mm <sup>2</sup> /s	13.70
Viscosity -25°C	mPas	4930
Viscosity index		154
Flash point COC	°C	224
Pour point	°C	-39
Total base number	mgKOH/g	10.4
Sulphated ash content	%	1.31

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

## PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be