

GOLD C3 5W40



This is a full synthetic lubricant based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides reliable protection of after-treatment devices and Diesel Particulate Filters. The oil is very universal in use and can be used for petrol and diesel engines.



APPLICATIONS

Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines. This 5W40 oil is also perfect for the lubrication of the latest generation Petrol cars.

PERFORMANCE LEVEL

- ACEA: C3
- API: SN, API SN Plus
- BMW: LONGLIFE-04
- FIAT: 9.55535-T2
- FORD: WSS-M2C917-A
- MB: 229.31/229.51/229.52
- GM dexos 2
- PORSCHE: A40
- RENAULT: RN 0700
- RENAULT: RN 0710
- VW: 502.00
- VW: 505.00
- VW: 505.01
- FIAT: 9.55535-S2

CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.850
Viscosity 40°C	mm ² /s	82.80
Viscosity 100°C	mm ² /s	14.00
Viscosity -30°C	mPas	5500
Viscosity index		175
Flash point COC	°C	232
Pour point	°C	-42
Total base number	mgKOH/g	7.4
Sulphated ash content	%	0.77

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be