

GOLD EF 5W/30



This is a full synthetic lubricant based on carefully selected very high quality base oils. This is a "LOW SAPS" oil for gasoline/LPG and diesel engines of passenger cars with or without turbo, requiring the lowest level of sulphated ash, phosphorus and sulfur and providing fuel economy.



APPLICATIONS

This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy. This engine oil can also be used, where ILSAC GF-4 oils are recommended.

PERFORMANCE LEVEL

- ACEA: C1
- JAGUAR / LAND ROVER STJR.03.5005

CHARACTERISTICS

| | Unit | Average Value |
|-----------------------|--------------------|---------------|
| Density at 15°C | kg/l | 0.847 |
| Viscosity 40°C | mm ² /s | 52.50 |
| Viscosity 100°C | mm ² /s | 9.46 |
| Viscosity -30°C | mPas | 3900 |
| Viscosity index | | 166 |
| Flash point COC | °C | 224 |
| Pour point | °C | -39 |
| Total base number | mgKOH/g | 6.6 |
| Sulphated ash content | % | 0.45 |

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be