

## GOLD F 5W30



This is a full synthetic lubricant based on carefully selected very high quality base oils, especially developed for the requirements of Ford WSS-M2C913-C/D specifications. It is characterized by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.



### APPLICATIONS

It is mandatory for all Ford models (gasoline and diesel, also those with particulate filter) from 2009 onwards. It's also required for the vehicles equipped with the 2,2 Duratorq TDCI engines and is fully backwards compatible with all current Ford diesel engines, with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford KA (diesel and gasoline from 2009).

### PERFORMANCE LEVEL

- **ACEA: A1-B1 / A5-B5**
- **API: SL/CF**
- **FORD: WSS-M2C913-C/D**
- **RENAULT: RN 0700**
- **JAGUAR / LAND ROVER STJLR.03.5003**

### CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.853
Viscosity 40°C	mm <sup>2</sup> /s	53.30
Viscosity 100°C	mm <sup>2</sup> /s	9.66
Viscosity -30°C	mPas	4200
Viscosity index		168
Flash point COC	°C	220
Pour point	°C	-45
Total base number	mgKOH/g	10.1
Sulphated ash content	%	1.09

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

### PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E [info@pen1one.be](mailto:info@pen1one.be)