

GOLD MAX 5W40



This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.



APPLICATIONS

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

PERFORMANCE LEVEL

- **ACEA: A3/B4**
- **API: SN/CF**
- **BMW: LONGLIFE-01**
- **MB: 226.5**
- **MB: 229.3**
- **OPEL: GM-LL-B-025**
- **Fiat 9.55535-M2**
- **PORSCHE: A40**
- **PSA: B71 2296**
- **RENAULT: RN 0700**
- **RENAULT: RN 0710**
- **VW: 502 00**
- **VW: 505 00**
- **VW: 505 01**

CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.853
Viscosity 40°C	mm ² /s	90.2
Viscosity 100°C	mm ² /s	15
Viscosity -30°C	mPas	5740
Viscosity index		175
Flash point COC	°C	223
Pour point	°C	-42
Total base number	mgKOH/g	10.5
Sulphated ash content	%	1.33

PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be