

## GREEN G2 5W30



A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming



### APPLICATIONS

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2

### PERFORMANCE LEVEL

- **API: SP Resource Conserving**
- **ILSAC: GF-6A**
- **GM: DEXOS 1 (TM) GEN 2**
- **CHRYSLER: MS6395**
- **FORD: WSS-M2C946-A / WSS-M2C961-A1**

### CHARACTERISTICS

	Unit	Average Value
Density at 15°C	kg/l	0.847
Viscosity 40°C	mm <sup>2</sup> /s	60.3
Viscosity 100°C	mm <sup>2</sup> /s	10.7
Viscosity -30°C	mPas	4500
Viscosity index		168
Flash point COC	°C	221
Pour point	°C	-36
Total base number	mgKOH/g	8.5
Sulphated ash content	%	0.94
HTHS (High Temperature High Shear)	mPa.s	2.97

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

### PEN1ONE

Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be