# ANTI-FREEZE XTRA G12+

A "longlife" OAT (Organic Additives Technology) anti-freeze based on monoethyleneglycol and selected additives to obtain the following properties:
- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behaviour towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free




## APPLICATIONS

May be used all the year round in cooling systems of gasoline and diesel engines. This anti-freeze should be diluted with demineralized water before use, in accordance with the ratio in the owner's manual or given below.

| Volume Alu-Freeze G12+ | 33% | 50% | 67% |
|---|---|---|---|
| Freezing point °c | -20°C | -40°C | -70°C |

It is recommended that at least 33% should be ALU-FREEZE G12+. Do not use in proportions above 70%

## PERFORMANCE LEVEL

- **ASTMD D3306**
- **ASTM D 4985**
- **SAE J 1034**
- **BS 6580 (2010)**
- **AFNOR NF R15-601**
- **FFV HEFT R 443**
- **CUNA NC 956-16**
- **UNE 26361-88**
- **JIS K 2234**
- **NATO S 759**
- **CHRYSLER MS 9176**
- **CUMMINS CES 14603**
- **FORD ESE M97B49-A WSS-M97B44-D ESD M97 B49-A**
- **GM1899 M US 6277 M OPEL GM QL130100**
- **JOHN DEERE H 24 B1 & C1**
- **LEYLAND TRUCKS LTS 22 AF10**
- **MACK 014GS 17004**
- **MAN 248 324 (SNF) & B&W D 36 5600**
- **MERCEDES MB 325.3**
- **RENAULT 41-01-001-D**
- **VAG TL 774 D/F**
- **VOLVO VCS**

## CHARACTERISTICS

| | Unit | Average Value |
|---|---|---|
| Density at 15°C | kg/l | 1.124 |
| Color | | RED |

**PEN1ONE**
Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be

We reserve the right to change the general characteristics of our products in order to allow our customers to benefit from the latest advances in technology.

**PEN1ONE**
Ardeca NV- Oudenaardestraat 49 • 8570 Vichte • Belgium • T +32 56 72 62 29 • F +32 56 72 67 37 • E info@pen1one.be